

Osmoz control and signalling units: non-illuminated heads



Technical characteristics p. 321 and see e-catalogue

Supplied with a fixing ring
 IP 69, IP 69K except Cat.Nos 0 238 11/12/13 - IP 67 and Cat.Nos 0 239 80/82 - IP 66
 Conform to IEC 60947-5-1

| Pack | Cat.Nos | Spring return |
|------|----------|---|
| | | Flush |
| 10 | 0 238 00 | ○ White |
| 10 | 0 238 01 | ● Red |
| 10 | 0 238 02 | ● Green |
| 10 | 0 238 03 | ● Blue |
| 10 | 0 238 04 | ● Yellow |
| 10 | 0 238 06 | ● Black |
| 1 | 0 238 08 | ● Red engraved "O" |
| 1 | 0 238 09 | ● Green engraved "I" |
| | | Flush with shroud - IP 67 |
| 5 | 0 238 11 | ● Red |
| 5 | 0 238 12 | ● Green |
| 5 | 0 238 13 | ● Black |
| | | Projecting |
| 5 | 0 238 21 | ● Red |
| 1 | 0 238 22 | ● Green |
| 5 | 0 238 26 | ● Black |
| | | Mushroom head Ø40 |
| 10 | 0 238 34 | ● Red |
| 10 | 0 238 35 | ● Green |
| 10 | 0 238 36 | ● Black |
| 1 | 0 238 37 | ● Yellow |
| | | Twin touch - IP66 |
| | | Red engraved "O", green engraved "I" |
| 5 | 0 239 80 | Flush/Flush - Green/Red |
| 5 | 0 239 82 | Flush/Projecting - Green/Red |
| | | Stay-put mushroom heads |
| | | Push-pull emergency stop |
| 10 | 0 238 72 | ● Red - Ø40 |
| 1 | 0 238 76 | ● Black - Ø40 |
| | | Push-pull ISO 13850 emergency stop |
| 10 | 0 238 74 | ● Red - Ø40 |
| 1 | 0 238 94 | ● Red - Ø54 |
| | | With flag indicator "O - I" |
| 5 | 0 238 95 | ● Red - Ø54 |
| | | With flag indicator "STOP - I" |
| | | Push-turn emergency stop |
| 10 | 0 238 80 | ● Red - Ø32 |
| 1 | 0 238 81 | ● Black - Ø32 |
| 10 | 0 238 82 | ● Red - Ø40 |
| 1 | 0 238 83 | ● Black - Ø40 |
| | | Push-turn ISO 13850 emergency stop |
| 10 | 0 238 85 | ● Red - Ø40 |
| | | Emergency stop with key |
| 10 | 0 238 91 | ● Red - Ø40 |
| | | ISO 13850 emergency stop with key |
| 1 | 0 238 92 | ● Red - Ø40 |

| Pack | Cat.Nos | Selector switches | Positions |
|------|----------|-----------------------------|--|
| | | With standard handle | |
| 1 | 0 239 02 | ● Green | 2 stay-put positions - 45° |
| 10 | 0 239 03 | ● Black | |
| 1 | 0 239 04 | ● Grey | |
| 1 | 0 239 09 | ● Black | 2 positions with spring-return - 45° |
| 10 | 0 239 15 | ● Black | 2 stay-put positions - 90° |
| 1 | 0 239 21 | ● Red | 3 stay-put positions - 45° |
| 1 | 0 239 22 | ● Green | |
| 10 | 0 239 23 | ● Black | |
| 1 | 0 239 24 | ● Grey | |
| 1 | 0 239 26 | ● Black | 3 positions with spring-return from left to 0 - 45° |
| 1 | 0 239 27 | ● Black | 3 positions with spring-return from right to 0 - 45° |
| 5 | 0 239 28 | ● Black | 3 positions with spring-return to 0 - 45° |
| 1 | 0 239 29 | ● Black | 3 stay-put positions - 90° |

Weatherproof cabinets, p. 261

