

MAXPRO[®]



Non Contact Voltage Tester, Flashlight

- Voltage detection 12..300VAC
- Zero fire wire identification
- Continuity test function
- Audible alarm and visual indication
- Built-in LED flashlight
- Screwdriver function
- LCD display with backlight

Technology Parameters	
AC Voltage Range [Un]	12..300VAC, 50/60Hz
Measurement Error	±(5%+3)
Humidity	≤95%
Altitude	≤2000m
Operating Temperature	0..40°C
Safety Level	CAT.III 300V
Display	LCD, backlight
Power Supply	1xAAA battery (not included)
Mechanical Data	
Product Dimensions	147x27x23mm
Product Weight	38g
Housing	thermoplastic
Indication	Sound & light double alarm
Low Battery Indication	Yes
Auto Power Off	Yes
Clip	Integrated pen clip
Codes	
CN8 (HS)	90303090
EAN	4742455001589

Functions

- AC voltage detection
- Inductive non-contact measurement
- Battery polarity detection
- Zero-fire line test
- Continuity test
- Breakpoint detection
- Flashlight lighting
- Button operation

Package Content

- 1x Voltage tester
- 1x Manual
- 1x Box

The manufacturer reserves the right to modify and/or improve the product without prior notice.

Elit OÜ

Akadeemia tee 78
12618 Tallinn, Estonia
Ph. +372 6229119

elit@elit.ee | www.elit.ee